

APPENDIX A Revision A	TRAILER MOUNTED SUPPORT SYSTEM PRODUCT DATA SHEET	
Company	DHS Systems LLC	
Part Number or NSN	1005103	Model: HP-4/3312, OD Green, Analog
Specifications as applicable	I	
Safety and Mobility Certification by Military Test Center		
Trailer		
Stowage Components included with trailer	NA	
Cargo Volume Stowage, For shelter and accessory components In cubic feet	140 cu. ft.	
Physical Dimensions for trailer	6.5 ft H	
Height	7.2 ft W	
Width	19 ft L	
Length		
Recommended Prime Mover Vehicle	LMTV	Requires a vehicle that can tow a 6,500 lb. trailer.
Empty GVW	5,292 lb.	
Tongue Weight	792 lb.	
Tire Type and Size	Radial	Two 37 x 12.50 x 16.5 LT Goodyear Wrangler R/T II, Load Rating C bias ply, run-flat tires
Fuel Tank Capacity	26 gal.	
Generator	l	
Nominal Output in kW, Volts AC, Hertz, Phase	33kW	120/208VAC, 60 Hz, 3-Phase.
Operating Environment	All	Operating Range: -50 °F to +140 °F.
Enginetype	Diesel	Four cylinder, turbo-charged, liquid cooled, direct injection, 1800 RP
Fuel Type	Diesel	Can also use JP8 or JP5.

Fuel Consumption	l NI A	
(AC Compressor On)	NA	
At 25% load	NA	
At 50% Load	NA	
At 75% Load	2.65	
at maximum output	Gal/hr.	
· ·	Gai/III.	
Noise in DB at 25 feet	NA	
(AC Compressor On)		
At 25% load	NA	
At 50% load	NA	
At 75% Load	76 dB	
At maximum rated load	' ' ' ' '	
Heater		
Nominal Output in BTU's	NA	
Electric Requirement		
Volts/Amps	NA	
Air Conditioning	,	
All Conditioning		
Maximum Cooling Capacityin		
BTU's	144,000 BT	
Maximum Heat Output		'
	2 stage hea	85,325 BTU/hr electric heat. 80,000 BTU/hr fuel fired AUX heat.
Capacity in BTU's	2 olago noc	
Refrigerant Type		
	R-407C	
CFM Air Flow		•
	4,300 CFM	
	1,000 0	
Air Duct Diameter		
	3 Ducts	One 18 in Supply, two 16 in Return.
	o D doile	
Power Requirements in kW, VAC, HZ,		
Phase	32 kW	
1		208 VAC, 60 Hz, 3-phase.
1		200 VAC, 00 Hz, 3-phase.
Special/Additional Features:		
	The HP-4/3312 Trailer provides three primary features for the end user of a larger DRASH shelter - cargo space, environmental control and power. It has a	
		oot cargo area, includes a 26 gallon fuel tank and comes with a 33 kW
	Genset and	12 Ton ECU.
	INCLUDES:	
	INCLUDES:	
	1 Drip Berm (T295188)	
	1 Trailer Electrical Set (T2-95235)	
	1 Trailer Push Package (TR35IG)	
	1 Supply Ducts (TG905-0151G, NSN 4720-01-558-9036)	
	2 Return Ducts (TG905-0001G, NSN 4720-01-558-7332)	
İ	1 Auxiliary Fuel Kit (T295180)	
		, ,
'		

(

(